

Performance Wall Mount Series



Today's home audio applications demand solutions which traditional designs are notable to fulfill. However, regardless of the installation, performance should never be compromised. The Performance Wall Mount Series are high performance wall mountspeakers which combine installation flexibility, simple elegant design, and renownedPSB sound.

Interior designers, architects, builders and system integrators will appreciate the elegance and highest performance levels offered by the Performance Wall Mount Series. Their slim profile allows them to hug the wall and maintain a minimal visual presence.

Beyond the visual appeal and ease of application is a sonic performance which lives up to the PSB heritage. Incorporating advanced driver and cabinet design, the PWM series offer open and constant dispersion, tonal balance and bass extension of a truly refined loudspeaker many times their size.

The PWM's can be oriented either vertically or horizontally and be used as a front left, right, centre or surround channel speakers. Whether as part of a complete on wall system, a basic TV application or as an on-wall centre channel solution for floor standing speakers; the PWM Series exceed expectations in every way.

- Slim Profile On-Wall speaker system
- All-new proprietary driver compliment
- Vertical or horizontal mounting options
- Wall mount bracket included
- LCR or for surround speaker application
- Design and final voicing engineered by Paul Barton
- Available in Satin White or Satin Black




Performance Wall Mount Series



| | PWM1 | PWM2 | PWM3 |
|---------------------------|--|--|--|
| Sensitivity | | | |
| Anechoic Chamber | 85dB | 86dB | 86dB |
| Typical Listening Room | 87dB | 89dB | 89dB |
| Frequency response | | | |
| On Axis +/- 3db | 70Hz-23kHz | 70Hz-23kHz | 60Hz-35kHz |
| LF Cutoff | 50Hz | 40Hz | 35Hz |
| Impedance | | | |
| Normal | 8 Ohms | 8 Ohms | 8 Ohms |
| Minimum | 6 Ohms | 6 Ohms | 6 Ohms |
| Acoustic Design | | | |
| Tweeter (Nominal) | 1" (25mm) Titanium Dome with Ferrofluid | 1" (25mm) Titanium Dome with Ferrofluid | 1" (25mm) Titanium Dome with Ferrofluid |
| Midrange (Nominal) | N/A | 2 x 3" (75mm) Carbon Fibre Cone Rubber Surround Cast Basket | 2 x 3" (75mm) Carbon Fibre Cone Rubber Surround Cast Basket |
| Woofers (Nominal) | 2 x 4" (100mm) Carbon Fibre Cone Rubber Surround Cast Basket | 2 x 4" (100mm) Carbon Fibre Cone Rubber Surround Cast Basket | 4 x 4" (100mm) Carbon Fibre Cone Rubber Surround Cast Basket |
| Design Type | Bass Reflex | Bass Reflex | Bass Reflex |
| Construction | | | |
| Cabinet | MDF | MDF | MDF |
| Grille Face | Cloth | Cloth | Cloth |
| Frame | MDF | MDF | MDF |

| | PWM1 | PWM2 | PWM3 |
|-----------------------------|----------------------------------|----------------------------------|---------------------------------|
| Dimensions | | | |
| Net H | 6.5" (165mm) | 6.5" (165mm) | 6.5" (165mm) |
| Net W | 28" (711mm) | 36" (914mm) | 48" (1219mm) |
| Net D | 3 3/8" (85mm) | 3 3/8" (85mm) | 3 3/8" (85mm) |
| Depth With Grill | 3 1/2" (90mm) | 3 1/2" (90mm) | 3 1/2" (90mm) |
| Shipping Information | | | |
| Dimensions | | | |
| Shipping H | 11 3/8" (288mm) | 11 3/8" (288mm) | 11 3/8" (288mm) |
| Shipping W | 32" (864mm) | 42" (1067mm) | 54" (1370mm) |
| Shipping D | 9" (228mm) | 9" (228mm) | 9" (228mm) |
| Volume | | | |
| | 2.02 cu ft (0.06m ³) | 2.49 cu ft (0.07m ³) | 3.2 cu ft (0.09m ³) |
| Weight | | | |
| Net | 14 lbs (6.4 kg) | 20 lbs (9.1 kg) | 26.5 lbs (12 kg) |
| Shipping | 20.1 lbs (9.1 kg) | 28 lbs (12.7 kg) | 33 lbs (15 kg) |
| Finish | | | |
| Available Finishes | Satin Black, Satin White | | |
| Grille Type | Magnetic, Cloth Grille | | |
| Wall Bracket | | | |

Wall Mount included for Vertical and Horizontal Mounting
Note: Bracket is not designed as ceiling mount



REAL SOUND for REAL PEOPLE
www.PSBspeakers.com